



International Journal of Advanced Research in Education and Technology (IJARETY)

Volume 13, Issue 3, May - June 2026

Impact Factor: 9.971



Secure Online Transaction Monitoring using Machine Learning

M.Rahul¹, Dr.J.Lourdu Xavier²

PG Scholar, Department of Master of Computer Applications, R.V.S. College of Engineering, Dindigul,
Tamil Nadu, India¹

Professor, Department of Master of Computer Applications, R.V.S. College of Engineering, Dindigul,
Tamil Nadu, India²

ABSTRACT: Financial fraud has emerged as one of the most critical challenges in the rapidly growing digital economy. With the exponential increase in online transactions, detecting fraudulent activities in real time has become a necessity for financial institutions and payment platforms. This paper proposes a machine learning-based system for secure online transaction monitoring that accurately detects fraudulent transactions while minimizing false positives. The system leverages ensemble learning techniques including XGBoost and Random Forest, combined with real-time data streaming frameworks for instant fraud detection. Implemented in Python using Scikit-learn and TensorFlow, the system achieves high detection accuracy by analyzing transaction patterns, user behavior, and contextual features. The proposed approach reduces financial losses, enhances trust in digital payment systems, and provides a scalable solution adaptable to evolving fraud patterns.

I. INTRODUCTION

The rapid growth of digital payment systems, e-commerce platforms, and online banking has transformed the global financial landscape. Millions of transactions occur every second across the world, making financial services more accessible than ever before. However, this digital transformation has also created new opportunities for fraudulent activities, leading to significant financial losses for individuals, businesses, and financial institutions.

Online payment fraud is a major concern in modern financial systems. Fraudsters continuously develop new strategies to exploit vulnerabilities in digital payment networks, making traditional rule-based fraud detection systems increasingly ineffective. These legacy systems are often unable to keep up with the dynamic nature of fraud, resulting in either high false positive rates that inconvenience legitimate customers or high false negative rates that allow fraudulent transactions to pass undetected.

Machine learning (ML) has emerged as a powerful tool for addressing these challenges. ML algorithms can automatically learn complex patterns from historical transaction data and generalize to detect new fraud patterns without explicit programming. Techniques such as Random Forest, XGBoost, Logistic Regression, and Neural Networks have demonstrated strong performance in fraud

detection tasks. Furthermore, the integration of real-time data processing frameworks enables immediate detection and alert generation, which is essential for minimizing financial losses.

This paper proposes an automated and intelligent online transaction monitoring system that employs advanced machine learning techniques for fraud detection. The system processes transaction data in real time, identifies suspicious patterns, and generates alerts for potentially fraudulent activities.

II. EXISTING SYSTEM

The existing system for detecting online transaction fraud using machine learning primarily relies on analyzing historical transaction data to identify patterns that differentiate fraudulent from legitimate activities. Typically, the system involves data preprocessing, feature engineering, and the application of classification algorithms such as Logistic Regression, Random Forest, Support Vector Machines (SVM), or XGBoost.

Python libraries including Pandas, Scikit-learn, NumPy, and Matplotlib are commonly used to clean data, train models, and evaluate performance using metrics such as accuracy, precision, recall, and ROC-AUC. Many existing systems utilize real-world datasets such as the Kaggle Credit Card Fraud Detection dataset to simulate and validate their models.

DISADVANTAGES

- **Inability to Detect New or Evolving Fraud Patterns:** Traditional static models cannot adapt to concept drift, meaning they fail to recognize newly emerging fraud strategies.
- **High False Positive Rate:** Existing systems often flag legitimate transactions as fraudulent, leading to customer dissatisfaction and operational overhead.
- **Lack of Real-Time Processing:** Most systems operate in batch mode and are unable to detect and respond to fraud at the moment of transaction.
- **Limited Scalability:** Traditional models struggle to handle the growing volume of digital transactions in a scalable and efficient manner.

III. PROPOSED SYSTEM

The proposed system aims to enhance the accuracy and efficiency of online transaction fraud detection by leveraging advanced machine learning techniques and real-time data processing. Unlike traditional systems, this model incorporates dynamic learning through techniques such as online learning and incremental model updates, enabling it to adapt to new fraud patterns (concept drift) as they emerge.

The system integrates ensemble methods like XGBoost and LightGBM, which offer superior predictive performance by combining multiple models. Real-time data streaming frameworks such as Apache Kafka or Spark Streaming are employed for immediate fraud detection and alert generation. Python remains the core development language, utilizing libraries such as Scikit-learn, TensorFlow, and PySpark.

ADVANTAGES

- **Real-Time Fraud Detection:** The system processes transactions instantly and generates alerts within milliseconds.
- **Improved Accuracy and Adaptability:** Ensemble models and incremental learning enable continuous improvement and adaptation to new fraud patterns.
- **Reduced False Positives:** Advanced feature engineering and threshold optimization minimize false alerts.
- **Scalability:** The distributed processing architecture handles high transaction volumes efficiently.

IV. SYSTEM ARCHITECTURE

The system architecture of the proposed fraud detection framework is designed as a multi-layered pipeline that enables continuous data ingestion, preprocessing, model inference, and alert generation. The architecture integrates both batch and stream processing capabilities to ensure both historical model training and real-time detection.

At the data ingestion layer, transaction data is captured from banking systems, payment gateways, and e-commerce platforms. This data flows into a preprocessing engine where it is cleaned, normalized, and transformed into feature vectors. The trained machine learning model evaluates each transaction, assigns a fraud probability score, and classifies it as legitimate or fraudulent.




Fig. 1: System Architecture of Secure Online Transaction Monitoring

V. MODULE DESCRIPTIONS

Data Collection Module

This module is responsible for collecting transaction data from diverse sources including banking APIs, payment gateways, and online platforms. The data includes key attributes such as transaction amount, timestamp, user identity, geographic location, device information, and merchant category. The Kaggle Credit Card Fraud Detection dataset, containing 284,807 transactions with a fraud rate of approximately 0.17%, is used as the primary dataset for training and evaluation.

Data Preprocessing & Feature Engineering

Raw transaction data undergoes comprehensive preprocessing in this module. Missing values are imputed, duplicate records are removed, and categorical variables are encoded. Given the highly imbalanced nature of fraud datasets, Synthetic Minority Over-sampling Technique (SMOTE) is applied to balance class distribution. Feature engineering creates informative attributes such as transaction frequency per user, average transaction amount, time since last transaction, and geographic deviation from user history.

Model Training & Evaluation

This module trains multiple machine learning models on the preprocessed dataset, including Logistic Regression, Random Forest, XGBoost, and LightGBM. The dataset is split into 80% training and 20% testing sets. A 5-fold cross-validation strategy is employed to assess model generalization. Performance is evaluated using accuracy, precision, recall, F1-score, and ROC-AUC.

Real-Time Fraud Detection Module

This module enables live transaction monitoring using the trained model. Each incoming transaction is immediately passed through the preprocessing pipeline, converted to a feature vector, and scored by the deployed model. Transactions exceeding a predefined fraud probability threshold are classified as fraudulent. The system leverages Spark Streaming or Apache Kafka for high-throughput, low-latency processing.

Alert & Model Update Module

Upon detection of a suspicious transaction, this module triggers automated alerts to users, fraud analysts, or system administrators through email, SMS, or dashboard notifications. Confirmed fraud cases are logged and used to periodically retrain the model through incremental learning techniques, ensuring the system remains accurate as fraud patterns evolve.

VI. RESULTS AND DISCUSSION

The proposed system was evaluated on the Kaggle Credit Card Fraud Detection dataset. The Jupyter Notebook-based Python implementation was used for all experiments. The following screenshots and output graphs illustrate the key results obtained during the evaluation of the system.




Fig. 2: Transaction Prediction - Jupyter Notebook Implementation (Python)

Figure 2 shows the Python code implemented in Jupyter Notebook for transaction prediction. The code loads the credit card dataset and generates a histogram comparing normal and fraudulent transactions over time. The seaborn library is used to visualize the distribution of transaction classes.




Fig. 3: Transactions Over Time - Normal vs Fraud Distribution

Figure 3 illustrates the distribution of normal (green) and fraudulent (red) transactions over time in seconds. The histogram clearly demonstrates the high imbalance between normal and fraudulent transactions, with fraudulent transactions being extremely rare compared to legitimate ones. This class imbalance is a key challenge addressed by the proposed system using SMOTE resampling techniques.




Fig. 4: Fraud Detection - Transaction Amount vs Time Scatter Plot and Amount Distribution

Figure 4 presents a scatter plot of fraudulent transaction amounts against time, along with a density distribution of transaction amounts. The scatter plot reveals that fraudulent transactions occur across all time periods with varying amounts, while the distribution plot shows that most fraudulent transactions involve relatively smaller amounts concentrated near zero, indicating that fraudsters often attempt smaller transactions to evade detection.




Fig. 5: Number of Fraudulent Transactions by Hour of Day

Figure 5 depicts the distribution of fraudulent transactions across different hours of the day. The bar chart reveals that fraud activity peaks during certain hours, particularly at 2:00 AM, 11:00 AM, and 18:00 (6 PM), suggesting that fraudsters are most active during late night and specific daytime windows. This temporal pattern is a critical feature utilized by the real-time detection module for enhanced fraud identification.

Table 1: Model Performance Comparison

Algorithm	Accuracy	Precision	Recall	F1-Score
Logistic Regression	94.3%	91.2%	88.5%	89.8%
Random Forest	97.8%	96.4%	94.1%	95.2%
SVM	95.6%	93.7%	90.8%	92.2%
XGBoost (Proposed)	99.2%	98.5%	97.9%	98.2%
LightGBM	98.7%	97.8%	96.5%	97.1%

The results confirm that the proposed XGBoost-based system significantly outperforms traditional approaches. The high recall value of 97.9% indicates that the system successfully identifies the vast majority of fraudulent transactions, while the precision of 98.5% ensures minimal disruption to legitimate users. The ROC-AUC score of 0.98 further validates the model's discriminative capability.

VII. CONCLUSION

This paper presented an intelligent and automated online transaction monitoring system utilizing machine learning for real-time fraud detection. The proposed system addresses the critical limitations of existing approaches by incorporating ensemble learning models, dynamic feature engineering, real-time stream processing, and adaptive model update mechanisms.

The XGBoost-based classifier achieved an accuracy of 99.2% and an F1-score of 98.2% on the Kaggle Credit Card Fraud Detection dataset, demonstrating its superior ability to identify fraudulent transactions with minimal false positives. The visualizations from the Jupyter Notebook implementation clearly demonstrate the temporal patterns and transaction amount distributions that the model successfully learns to exploit for fraud detection.

The proposed system provides a scalable, cost-effective, and reliable solution for fraud detection in modern digital payment environments. It holds significant promise for deployment in banking systems, e-commerce platforms, and fintech applications to enhance financial security and user trust.

VIII. FUTURE ENHANCEMENTS

Several enhancements can further improve the proposed system. The model can be trained on larger, more diverse datasets encompassing various geographic regions and transaction types to improve generalization. Deep learning architectures such as LSTM and Transformer networks can be explored to capture temporal dependencies in sequential transaction data.

The system can also be extended to incorporate graph-based fraud detection techniques that model relationships between users, merchants, and devices to uncover coordinated fraud rings. Integration with mobile and web platforms via RESTful APIs would allow real-time fraud screening to be embedded directly into payment applications. Additionally, the adoption of federated learning would enable collaborative model training across multiple financial institutions without sharing sensitive customer data.

REFERENCES

1. V. Bhusari and S. Patil, "Study of Hidden Markov Model in Credit Card Fraudulent Detection," International Journal of Computer Applications, vol. 20, no. 5, pp. 33–37, Apr. 2011.
2. A. Dal Pozzolo, O. Caelen, R. A. Johnson, and G. Bontempi, "Calibrating Probability with Undersampling for Unbalanced Classification," in IEEE Symposium Series on Computational Intelligence, 2015, pp. 159–166.
3. S. Jha, M. Guillen, and J. C. Westland, "Employing Transaction Aggregation Strategy to Detect Credit Card Fraud," Expert Systems with Applications, vol. 39, no. 16, pp. 12650–12657, 2012.
4. A. Ngai, Y. Hu, Y. Wong, Y. Chen, and X. Sun, "The Application of Data Mining Techniques in Financial Fraud Detection: A Classification Framework and an Academic Review of Literature," Decision Support Systems, vol. 50, no. 3, pp. 559–569, 2011.
5. A. Phua, V. Lee, K. Smith, and R. Gayler, "A Comprehensive Survey of Data Mining-Based Fraud Detection Research," Artificial Intelligence Review, vol. 34, no. 1, pp. 1–14, 2010.
6. S. Duman and M. H. Ozcelik, "Detecting Credit Card Fraud by ANN and Logistic Regression," in International Symposium on Innovations in Intelligent Systems and Applications, 2011, pp. 315–319.
7. A. Srivastava, A. Kundu, S. Sural, and A. Majumdar, "Credit Card Fraud Detection Using Hidden Markov Model," IEEE Transactions on Dependable and Secure Computing, vol. 5, no. 1, pp. 37–48, 2008.
8. J. West and M. Bhattacharya, "Intelligent Financial Fraud Detection: A Comprehensive Review," Computers & Security, vol. 57, pp. 47–66, 2016.
9. G. Bolton and D. Hand, "Statistical Fraud Detection: A Review," Statistical Science, vol. 17, no. 3, pp. 235–255, 2002.
10. T. Chen, C. Guestrin, "XGBoost: A Scalable Tree Boosting System," in Proceedings of the 22nd ACM SIGKDD Conference, 2016, pp. 785–794.
11. L. Breiman, "Random Forests," Machine Learning, vol. 45, no. 1, pp. 5–32, 2001.
12. F. Pedregosa et al., "Scikit-learn: Machine Learning in Python," Journal of Machine Learning Research, vol. 12, pp. 2825–2830, 2011.
13. Goodfellow, Y. Bengio, and A. Courville, Deep Learning, MIT Press, 2016.
14. Han, M. Kamber, and J. Pei, Data Mining: Concepts and Techniques, 3rd ed., Morgan Kaufmann, 2011.
15. T. Fawcett, "An Introduction to ROC Analysis," Pattern Recognition Letters, vol. 27, no. 8, pp. 861–874, 2006.



International Journal of Advanced Research in Education and Technology

ISSN: 2394-2975

Impact Factor: 9.971